

PROZONE[®]

OZONE GENERATOR - CERAMIC PLATE
TECHNOLOGY

Features and Benefits



- Destroys harmful micro-organisms.
- Kills up to 99.5% of airborne bacteria, eliminates bad odours and smells.
- Programmable or non programmable versions available - for 24/7 use or to suit location conditions.
- **Suitable for either portable or fixed** installation, for use in areas such as hotels, nursing homes, hospitals etc.
- Offers excellent cost in use, consuming only 14 watts of electricity.
- Produces ozone gas within European guidelines, penetrating to even the most inaccessible locations.
- Approved by TÜV SÜD to the standard BS/ EN60335 parts 1 and 2- the first ever ozone generator to achieve this standard.
- Part of a co-ordinated washroom range.



PhilClassic

for hygiene

CONTACT DETAILS

Cell: +27(0) 81 431 2625

E-mail: philclassic@lantic.net

PROZONE[®]

OZONE GENERATOR

Product Specifications

Dimensions:
210mm (H) x 135mm (W) x 85mm (D)

Operation:
100/240 VAC.

Installation options:
Fixed or portable application.

TÜV SÜD and CE Approved

Standards:
EN 60335-2-65/A1:2008
EN 60335-1/A15:2001
EN 62233:2008

Voltage:
100-240V / 50/60 Hz / Fuse rating 5A.

Power rating:
14 watts.

Weight:
1kg (approx.)



PhilClassic

for hygiene

CONTACT DETAILS

Cell: +27(0) 81 431 2625

E-mail: philclassic@lantic.net